



Prime-All UV

EXTERIOR - WATER BASED

Transparent Primer and Sealer for all exterior timber

PRODUCT DESCRIPTION

Boscote Prime-All UV is a Cedar tone transparent, water-based primer/ sealer and stabiliser for exterior timber. **Prime-All UV** increases protection of timber by filtering UV light and prevents fading and cellulose fibre breakdown. **Prime-All UV** contains fungicides for protection against mould and mildew attack. It is designed for easy penetration into timber pores. **Prime-All UV** protects timber by resisting ultra violet light, water penetration, mould, mildew, fungi, sap stains, checking, cupping, splitting and dry rot.

RECOMMENDED USES

Prime-All UV is recommended for all timber where increased UV protection is warranted. **Prime All UV** also eases the application of topcoats and is suitable for back priming weatherboards and improving the adhesion of **Boscote Cladcoat** and **Boscote Decks**. **Prime All UV** is tintable to a wide range of timber tones.

Note: **Prime-all UV** is not recommended for long- term exposure without the addition of **Decks** or **Cladcoat**. If **Prime-All UV** were to be used for short- term protection, a period of about 3 months would be the recommended maximum exposure time dependant on aspect and timber species. Immediately after this period the surface should be thoroughly cleaned, recoated and top coated with **Decks**, **Cladcoat** or any other compatible acrylic coating. If the exposure period exceeds 3 months, thoroughly clean the surface with **Boscote Woodwash** and water then apply a further coat of **Prime-All UV** prior to top coating.

DIRECTIONS FOR USE

Because of its thin consistency **Prime-All UV** is easy to apply. It can be applied using a paintbrush, a flat lambswool applicator, a paint roller, a spray gun or dipping. No thinning is necessary when spraying.

If the timber is dense and oily or showing visible tannin stains and water marks it should be cleaned with **Woodwash** to remove any water-soluble extractives that are contained in the timber. This will ensure a clean stable surface.

- Step 1 Stir contents of can thoroughly before and during use. Do not thin or shake can.
- Step 2 Apply a wet on wet or saturation coat to all exposed timber surfaces. Ensuring all edges and end grains are thoroughly coated.
- Step 3 Allow to dry for minimum of four hours before applying Boscote Decks or Cladcoat.

SURFACE PREPARATION

IMPORTANT: All timbers are different, please read the preparation instructions for details on how to treat different timbers. For further information on Boscote Timber Coatings please refer to the Boscote website or the Technical Data Sheet.

PRECAUTIONS

Bostik does not recommend thinning or mixing any of its products with other coatings or products from other manufacturers.

See technical data sheets for further information.

- **PENETRATING PRIMER/ SEALER**
- **SUITABLE FOR TIMBER DECKS, CLADDING AND OUTDOOR FURNITURE**
- **INCREASE THE DURABILITY OF THE FINISH COAT**
- **PROTECTION AGAINST MOULD AND FUNGI ATTACK**
- **PRE-CONSTRUCTION PRIMER**

BASIC DATA

Gloss Level	Satin
Colour	Transparent – Natural Cedar tone
Drying Time	20 minutes touch dry
Recoat Time	4 hours
Clean Up	Water
Coverage	2-4m ² per litre rough sawn timber* 6-8m ² per litre dressed timber*
Low VOC	60g/L

*Coverage rates are estimates only as timber species and application technique can affect the coverage rate of this product. This product should not be applied on days when the temperatures are below 10°C or above 30°C.

